

SPECIFICATION

For

YK NYY

450/750V 70°C Copper Conductor PVC Insulated
PVC Inner Sheathed PVC Outer Sheathed Super Soft Power Cable
(450/750V, Cu /PVC/PVC/PVC)

BY Wachara
(Wachara Sangsomritphon)

MANAGER, Cable Design Section

APP. Winai Ariyasakulsap
(Winai Ariyasakulsap)
MANAGER, Development Department

Rev.	Date	Description
0	10/11/2019	Issued specification

APP. _____
()
CUSTOMER

Customer Document	Rev.

Remark:

This document is based on the Customer Document for the structure and properties of electric wire and cable only. If there are different points, will be shown in deviation table.

1. Scope

This specification covers 450/750V copper conductor polyvinyl chloride (PVC) insulated polyvinyl chloride (PVC) inner sheathed polyvinyl chloride (PVC) outer sheathed super soft power cable.

Maximum conductor temperature shall be 70°C.

The cable shall be in accordance with TIS 11 Part 101-2559, Table 3 and Table 4.

Flame retardant test TIS 11 Part 2-2553 (Same IEC 60332-1 : 2015).

2. Conductor

For size $\leq 10\text{mm}^2$:

The conductor shall be non-compacted concentric stranded uncoated annealed copper conductor in accordance with TIS 2427-2552, Class 2.

The direction of lay shall be left-hand (S) lay.

For size $\geq 16\text{mm}^2$:

The conductor shall be compacted concentric stranded uncoated annealed copper conductor in accordance with TIS 2427-2552, Class 2.

The direction of lay shall be left-hand (S) lay in the outermost layer.

3. Insulation

The insulation shall be polyvinyl chloride (PVC/C) compound meet the requirements of TIS 11 Part 101-2559.

The average thickness of the insulation shall be not less than that given in Table 1.

The minimum thickness shall not fall below the value in Table 1 by more than 10% plus 0.1 mm.

4. Cabling (For multi-core only)

The individual insulated cores shall be cabled together with suitable length of lay or PVC rod to give the completed cable a circular cross section.

The direction of lay shall be left-hand (S) lay.

5. Core Identification

The cores shall be identified by colors, as follows :

Single-core : black

2-cores : blue, brown

3-cores : brown, black, grey

4-cores : blue, brown, black, grey

6. Inner Sheath (For multi-core only)

The inner sheath shall be polyvinyl chloride (PVC) compound applied over the cable core.

The approximate thickness given in Table 1.

The color of the inner sheath shall be black.

7. Outer Sheath

The outer sheath shall be polyvinyl chloride (PVC/ST4) compound meet the requirements of TIS 11 Part 101-2559.


The average thickness of the outer sheath shall be not less than that given in Table 1.

The minimum thickness shall not fall below the value in Table 1 by more than 15% plus 0.1 mm.

The color of the outer sheath shall be black.

8. Marking on Cable

The marking items shall be marked with suitable mean throughout the length of cable.

1. Manufacturer's name and/or trade mark "  YAZAKI.....: TYE"
2. Designation "YK NYY"
3. Rated voltage "450/750V"
4. Insulation and sheath material "PVC/PVC"
5. Max. operating rated temperature at conductor "70°C"
6. Number of core and size of conductor
7. TIS logo and standard number
8. The continuous reel length marking (in figure) shall be made on the outer sheath at every 1 meter (Except single core cable, the length mark on size $\geq 10 \text{ mm}^2$)

9. Test and Properties


The cable shall be meet the requirement in Test and Inspection and Table 1, when tested in accordance with TIS 11 Part 101-2559 and TIS 2427-2552 and TIS 11 Part 2-2553 (Same IEC 60332-1 : 2015).

10. Packing

The cable shall be placed on non-returnable wooden reels.

The reels shall be covered with suitable covering to provide the cable with physical protection during transportation and during ordinary storage and handling operations.

Each reel shall be clearly marked as follows.

1. Rated voltage "450/750V "
2. Max. operating rated temperature at conductor "70°C"
3. Designation "YK NYY"
4. Number of core and size of conductor
5. Cable length
6. Net and gross weight
7. Month and year of manufacture
8. Rolling direction of reel
9. Manufacturer's name and/or trade mark "  YAZAKI "

Test and Inspection

Sample Tests

- Maximum conductor resistance, Ohm/km specified in Table 1
- AC test voltage for 5 minutes, kV2.5
- Construction.....specified in Table 1

Type Tests

This cable shall be tested as followed :

- Minimum insulation resistance at 70 °C, MOhm-km specified in Table 1
- Flame retardant tested according to TIS 11 Part 2-2553 (Same IEC 60332-1)

Definition concerning the tests


Routine tests: Tests made by the manufacturer on each manufactured length of cable to check that each length meets the specified requirements.

Sample tests: Tests made by the manufacturer on samples of completed cable or components taken from a completed cable, at a specified frequency, so as to verify that the finished product meets the specified requirements.

Type tests: Tests made before supplying, on a general commercial basis, a type of cable covered by this standard, in order to demonstrate satisfactory performance characteristics to meet the intended application.

Cable structure

Cross-sectional (Not scale)



No.	Structure	Material
1	Conductor	Compacted concentric stranded annealed copper
2	Insulation	Polyvinyl chloride (PVC/C)
3	Filler	PVC Rod
4	Inner Sheath	Polyvinyl chloride (PVC)
5	Outer Sheath	Polyvinyl chloride (PVC/ST4)

Application: For installation exposed, or in raceway, wet or dry location, or direct burial in ground, Maximum conductor temperature of 70°C for normal operation and 160°C for short circuit condition.

Table 1

No. of core	Size (mm ²)	Conductor		Insulation thickness nominal (mm)	Sheath thickness nominal (mm)	Overall diameter maximum (mm)	Conductor resistance at 20 °C maximum (Ohm/km)	Insulation resistance at 70 °C minimum (MOhm-km)	Weight of cable approx. (kg/km)	Standard packing length (m)	
		No. of wires (wires)	Type							1000	2000
1	6	7	Non-compacted	1.5	1.8	11.0	3.08	0.0107	170	1000	2000
1	10	7	Non-compacted	1.5	1.8	12.0	1.83	0.0088	230	1000	2000
1	16	7	Compacted	1.5	1.8	13.0	1.15	0.0074	290	1000	2000
1	25	7	Compacted	1.5	1.8	14.5	0.727	0.0061	390	1000	2000
1	35	7	Compacted	1.5	1.8	16.0	0.524	0.0053	490	1000	2000
1	50	19	Compacted	1.5	1.8	17.0	0.387	0.0046	600	1000	2000
1	70	19	Compacted	1.5	1.8	19.0	0.268	0.0039	850	1000	2000
1	95	19	Compacted	1.7	1.8	21.5	0.193	0.0038	1100	1000	2000
1	120	37	Compacted	1.7	1.8	23.0	0.153	0.0034	1300	1000	2000
1	150	37	Compacted	1.9	2.0	26.0	0.124	0.0034	1600	1000	2000
1	185	37	Compacted	2.1	2.0	28.0	0.0991	0.0034	2000	1000	2000
1	240	37	Compacted	2.3	2.2	31.5	0.0754	0.0033	2800	1000	1200

Table 1 (continued)

No. of cores	Size (mm ²)	Conductor			Insulation thickness nominal (mm)	Inner sheath thickness approx. (mm)	Outer sheath thickness nominal (mm)	Overall diameter maximum (mm)	Conductor resistance at 20 °C maximum (Ohm/km)	Insulation resistance at 70 °C minimum (MOhm-km)	Weight of cable approx. (kg/km)	Standard packing length (m)
		No. of wires (wires)	Type	Diameter approx. (mm)								
2	6	7	Non-compacted	3.09	0.9	0.8	1.8	17.0	3.08	0.0073	370	1000
2	10	7	Non-compacted	3.99	1.1	0.8	1.8	19.5	1.83	0.0069	550	1000
2	16	7	Compacted	4.80	1.1	0.8	2.0	22.5	1.15	0.0057	1000	2000
2	25	7	Compacted	6.10	1.3	1.2	2.0	27.0	0.727	0.0054	1000	2000
2	35	7	Compacted	7.10	1.3	1.2	2.0	29.5	0.524	0.0047	1000	2000
2	50	19	Compacted	8.20	1.5	1.2	2.2	33.5	0.387	0.0046	1700	1000
2	70	19	Compacted	9.90	1.5	1.5	2.2	38.0	0.268	0.0039	2300	1000

Table 1 (continued)

No. of cores	Size (mm ²)	Conductor			Insulation thickness nominal (mm)	Inner sheath thickness approx. (mm)	Outer sheath thickness nominal (mm)	Overall diameter maximum (mm)	Conductor resistance at 20 °C maximum (Ohm/km)	Insulation resistance at 70 °C minimum (MOhm-km)	Weight of cable approx. (kg/km)	Standard packing length (m)
		No. of wires	Type	Diameter approx. (mm)								
3	6	7	Non-compacted	3.09	0.9	0.8	1.8	18.0	3.08	0.0073	440	1000
3	10	7	Non-compacted	3.99	1.1	0.8	1.8	20.5	1.83	0.0069	650	1000
3	16	7	Compacted	4.80	1.1	1.2	2.0	24.5	1.15	0.0057	900	1000
3	25	7	Compacted	6.10	1.3	1.2	2.0	28.5	0.727	0.0054	1300	1000
3	35	7	Compacted	7.10	1.3	1.2	2.0	31.5	0.524	0.0047	1600	1000
3	50	19	Compacted	8.20	1.5	1.5	2.2	36.0	0.387	0.0046	2200	1000
3	70	19	Compacted	9.90	1.5	1.5	2.2	40.5	0.268	0.0039	2900	1000

Table 1 (continued)

No. of cores	Size (mm ²)	Conductor			Insulation thickness nominal (mm)	Inner sheath thickness approx. (mm)	Outer sheath thickness nominal (mm)	Overall diameter maximum (mm)	Conductor resistance at 20 °C maximum (Ohm/km)	Insulation resistance at 70 °C minimum (MOhm-km)	Weight of cable approx. (kg/km)	Standard packing length (m)
		No. of wires (wires)	Type	Diameter approx. (mm)								
4	6	7	Non-compacted	3.09	0.9	0.8	1.8	19.0	3.08	0.0073	550	1000
4	10	7	Non-compacted	3.99	1.1	0.8	2.0	23.0	1.83	0.0069	800	1000
4	16	7	Compacted	4.80	1.1	1.2	2.0	26.5	1.15	0.0057	1100	1000
4	25	7	Compacted	6.10	1.3	1.2	2.0	31.0	0.727	0.0054	1600	1000
4	35	7	Compacted	7.10	1.3	1.5	2.2	35.0	0.524	0.0047	2100	1000
4	50	19	Compacted	8.20	1.5	1.5	2.2	39.5	0.387	0.0046	2800	1000
4	70	19	Compacted	9.90	1.5	1.5	2.4	44.5	0.268	0.0039	3700	800